

SILITERM 500°C**Safety data sheet****SECTION 1. Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**Code: 8130_A_
Product name: SILITERM 500°C**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use: Not available

1.3. Details of the supplier of the safety data sheetName: COLORIFICIO SAMMARINESE S.p.A.
Full address: Via del Camerario, 7
District and Country: 47891 Falciano RSM
Tel.: +378 0549 905515
Fax: +378 0549 908453

e-mail address of the competent person responsible for the Safety Data Sheet: sds@colsam.com

Product distribution by: COLORIFICIO SAMMARINESE S.p.A.

1.4. Emergency telephone numberFor urgent inquiries refer to:
TEL. +378 0549 905515 (dalle ore 08.30 alle ore 17.30 - Lunedì / Venerdì) Di seguito si riportano i principali Centri Antiveleño presenti in Italia ed operativi 24 ore su 24, con i recapiti telefonici utili per contattarli tempestivamente:
TORINO: Centro Antiveleño - Azienda Ospedaliera "S.G. Battista"- Molinette di Torino - Tel. 011 6637637
MILANO: Centro Antiveleño - Ospedale Niguarda Ca' Granda - Tel. 02 66101029
PAVIA: Cen. Naz. Inform. Tossic. Fond. S. Maugeri- Clinica del Lavoro e della Riabilitazione - Tel. 0382 24444
PADOVA: Serv. Antiv. - Cen. Interdipartimentale di Ricerca sulle Intossicazioni Acute Dip. di Farmac. E.Meneghetti Università degli Studi di Padova – Tel. 049/8275078
GENOVA: Servizio Antiveleño Serv.Pr.Socc.,Accett. e Oss. Istituto Scientifico G. Gaslini – TEL. 010/5636245
FIRENZE: Centro Antiveleño - U.O. Tossicologia Medica Azienda Ospedaliera Careggi - TEL. 055/4277238
ROMA: Centro Antiveleño Policlinico A.Gemelli - Università Cattolica Del Sacro Cuore - TEL. 06/3054343
ROMA:Centro Antiveleño - Istituto Di Anestesiologia E Rianimazione Università Degli Studi Di Roma La Sapienza – TEL. 06/49970698 06/4461967
NAPOLI: Centro Antiveleño Azienda Ospedaliera A. Cardarelli– TEL. 081/7472870**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

SILITERM 500°C

SECTION 2. Hazards identification ... / >>

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P201	Obtain special instructions before use.
P210	Keep away from heat / sparks / open flames / hot surfaces. No smoking.
P233	Keep container tightly closed.
P280	Wear protective gloves / clothing and eye / face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.

Contains: TOLUENE
XYLENE
HYDROCARBONS, C9, AROMATICS
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	Conc. %	Classification 1272/2008 (CLP)
XYLENE		
CAS 1330-20-7	22 - 23,5	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Note C
EC 215-535-7		
INDEX 601-022-00-9		
Reg. no. 01-2119488216-32		

SILITERM 500°C**SECTION 3. Composition/information on ingredients** ... / >>**HYDROCARBONS, C9, AROMATICS**

CAS 9 - 10 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336,
Aquatic Chronic 2 H411, EUH066, Note 4 P

EC 918-668-5

INDEX

Reg. no. 01-2119455851-35

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

CAS 6 - 7 Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066, Note 4 P

EC 919-857-5

INDEX

Reg. no. 01-2119463258-33

TOLUENE

CAS 108-88-3 4 - 4,5 Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315,
STOT SE 3 H336

EC 203-625-9

INDEX 601-021-00-3

Reg. no. 01-2119471310-51

QUARTZ

CAS 14808-60-7 1,5 - 2 STOT RE 2 H373

EC 238-878-4

INDEX

ETHYLBENZENE

CAS 100-41-4 1 - 1,5 Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373

EC 202-849-4

INDEX 601-023-00-4

Reg. no. 01-2119489370-35

Note: Upper limit is not included into the range

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media**

SUITABLE EXTINGUISHING EQUIPMENT

Chemical powder.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use water.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

No information available.

5.3. Advice for firefighters

GENERAL INFORMATION

Flammable gases develop in contact with water or moisture.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SILITERM 500°C**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Avoid leakage of the product into the environment. Work in adequately ventilated areas. Avoid flames and sparks. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store in a well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

Store only in the original container. Keep the product in clearly labelled containers. Keep containers well sealed. Avoid contact with water or that may absorb moisture at all costs. Avoid violent blows. Avoid overheating. Store in a ventilated and dry place, far away from sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015
FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ -ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
EU	OEL EU TLV-ACGIH	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC. ACGIH 2014

SILITERM 500°C

SECTION 8. Exposure controls/personal protection ... / >>
XYLENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	221	50	442	100	SKIN
VLEP	FRA	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	
TLV	GRC	435	100	650	150	
TLV	ITA	221	50	442	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH		434	100	651	150	

TOLUENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	192	50	384	100	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
TLV	GRC	192	50	384	100	
TLV	ITA	192	50			SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

QUARTZ
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	0,1				
VLEP	FRA	0,1				RESP
WEL	GBR	0,3				
TLV-ACGIH		0,025				

ETHYLBENZENE
Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	441	100	884	200	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
WEL	GBR	441	100	552	125	SKIN
TLV	GRC	435	100	545	125	
TLV	ITA	442	100	884	200	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

SILITERM 500°C

SECTION 8. Exposure controls/personal protection ... / >>

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance		viscous liquid
Colour		aluminum
Odour		typical organic substances
Odour threshold		Not available
pH		7 (neutro)
Melting point / freezing point		Not available
Initial boiling point	>	138 °C
Boiling range		Not available
Flash point	>	23 °C
Evaporation Rate		Not available
Flammability (solid, gas)		Not available
Lower inflammability limit		Not available
Upper inflammability limit		Not available
Lower explosive limit		Not available
Upper explosive limit		Not available
Vapour pressure		5 mmHg
Vapour density		>1
Relative density		1.26 - 1.18 A 20°C Kg/l
Solubility		Not available
Partition coefficient: n-octanol/water		Not available
Auto-ignition temperature	>	453 °C
Decomposition temperature		0
Viscosity		14.00 - 10.00 Viscosità tazza Ford n°8
Explosive properties		Not available
Oxidising properties		Not available

9.2. Other information

Solid content		54,88 %	
VOC (Directive 2010/75/EC) :		43,62 %	- 532,16 g/litre
VOC (volatile carbon) :		38,01 %	- 463,68 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

TOLUENE: breaks down in sunlight.

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.

XYLENE (MIXTURE OF ISOMERS): stable, but may develop violent reactions in the presence of strong oxidising agents such as sulphuric and nitric acids and perchlorates. May form explosive mixtures with the air.

TOLUENE: risk of explosion on contact with fuming sulphuric acid, nitric acid, silver perchlorates, nitrogen dioxide, non-metal halogenides, acetic acid, organic nitrocompounds. Can form explosive mixtures with the air. May react dangerously with: strong oxidising agents, strong acids, sulphur (in the presence of heat).

SILITERM 500°C**SECTION 10. Stability and reactivity ... / >>**

ETHYLBENZENE: reacts violently with strong oxidising agents and attacks various types of plastics. Can form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

ETHYLBENZENE: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information**11.1. Information on toxicological effects**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product must be handled carefully because of its possible teratogenic effects, which may be toxic and damage the foetus development.

The introduction of even small quantities of this liquid into the respiratory system in case of ingestion or vomit may cause bronchopneumonia and pulmonary edema.

This product may cause functional disorders or morphological mutations after repeated or prolonged exposure and/or may accumulate inside the human body and is thus graded as dangerous.

Acute effects: stinging eyes. Symptoms may include: rubescence, edema, pain and lachrymation. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

Acute effects: contact with skin may cause: irritation, erythema, edema, dryness and chapped skin. Ingestion may cause health disorders, including stomach pain and sting, nausea and sickness.

Acute effects: inhalation of this product may irritate the lower and upper respiratory tract and cause cough and respiratory disorders; at higher concentrations it can also cause pulmonary edema. Ingestion may cause health problems, including stomach pain and sting, nausea and sickness.

XYLENE (MIXTURE OF ISOMERS): has a toxic effect on the CNS (encephalopathies). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

TOLUENE: it has a toxic effect on the central and peripheral nervous system (with encephalopathies and polyneuritis). Irritating to the skin, conjunctivae, cornea and respiratory apparatus.

ETHYLBENZENE: like the benzene homologues, may exert an effect on the CNS with depression, narcosis, often preceded by dizziness and accompanied by headache. It is irritating to the skin, conjunctivae and respiratory apparatus.

XYLENE

LD50 (Oral)	3523 mg/kg Rat
LD50 (Dermal)	4350 mg/kg Rabbit
LC50 (Inhalation)	26 mg/l/4h Rat

TOLUENE

LD50 (Oral)	5580 mg/kg Rat
LD50 (Dermal)	12124 mg/kg Rabbit
LC50 (Inhalation)	28,1 mg/l/4h Rat

ETHYLBENZENE

LD50 (Oral)	3500 mg/kg Rat
LD50 (Dermal)	15354 mg/kg Rabbit
LC50 (Inhalation)	17,2 mg/l/4h Rat

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

SILITERM 500°C**SECTION 12. Ecological information** ... / >>

XYLENE	
Solubility in water	mg/l 100 - 1000
Biodegradability: Information not available	
TOLUENE	
Solubility in water	mg/l 100 - 1000
Rapidly biodegradable	
ETHYLBENZENE	
Solubility in water	mg/l 1000 - 10000
Rapidly biodegradable	

12.3. Bioaccumulative potential

XYLENE	
Partition coefficient: n-octanol/water	3,12
BCF	25,9
TOLUENE	
Partition coefficient: n-octanol/water	2,73
BCF	90
ETHYLBENZENE	
Partition coefficient: n-octanol/water	3,6

12.4. Mobility in soil

XYLENE	
Partition coefficient: soil/water	2,73

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID:	PAINT or PAINT RELATED MATERIAL
IMDG:	PAINT or PAINT RELATED MATERIAL
IATA:	PAINT or PAINT RELATED MATERIAL

SILITERM 500°C

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special Provision: 640E	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo: Pass.: Special Instructions:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso category 6

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>		
<u>Point</u>	3 - 40	
<u>Contained substance</u>		
<u>Point</u>	48	TOLUENE Reg. no.: 01-2119471310-51

Substances in Candidate List (Art. 59 REACH)

None

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

SILITERM 500°C**SECTION 15. Regulatory information ... / >>**

Product not intended for uses provided for by Dir. 2004/42/CE.

15.2. Chemical safety assessment

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

SILITERM 500°C**SECTION 16. Other information ... / >>**

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:

The following sections were modified:

01.