

SERIES **2286.0250 EPIC RIFF BASE COAT**
 2288.4200 EPIC RIFF RUST FINISH
 2288.4300 EPIC RIFF ALUMINIUM FINISH

Uses

EPIC RIFF is a metallic finish obtained thanks to a special mixture of micaceous iron, acrylic resins and semi-covering pigments. The application of the metallic patina, over a properly worked substrate, creates excellent aging effects on the surface, obtaining in this way a pleasant environment for any kind of furnishing.

Available in the following products:

2256.0250 - EPIC RIFF Base Coat, it can be tinted with the System Colormaker in the shades of the EPIC RIFF colour card

2288.4200 - EPIC RIFF Rust finish

2288.4300 - EPIC RIFF Aluminium finish, it can be tinted with the System Colormaker in the shades of the EPIC RIFF colour card

General features

Water-based acrylic finish for interiors with low V.O.C. content, with the following characteristics:

- Easy to apply;
- Great covering power;
- Excellent decorative quality.

Technical features (data gathered with 20°C)

2286.0250 EPIC RIFF BASE COAT

Brookfield Viscosity	cps	13000 ± 1000
Specific weight	kg/l	1,640 ± 0,050
Theoretical yield	m ² /l	1.4 ± 0.1 For two coats
Film appearance	gloss	matt
Thinner	code	water
Dry to touch	hours	3 - 4
Dry in depth	hours	24
Over paintable	hours	6 - 8

2288.4200 - 2288.4300 RIFF FINSH

Brookfield Viscosity	cps	1900 ± 100
Specific weight	kg/l	1.090 ± 0.050
Theoretical yield	m ² /l	4 - 5 For two coats
Film appearance	gloss	matt
Thinner	code	water
Dry to touch	hours	4 - 5
Dry in depth	hours	4 - 5
Over paintable	hours	8 - 12

Application methods

Rigid plastic trowel	EPIC RIFF Base Coat	Ready to use
Brush and sponge for glazing effects	EPIC RIFF Finish	Ready to use

Application cycle

NEW WALLS – Before the application make sure that the surface is well cohesive, clean and dry. In case of chalking surfaces it's necessary to use the fixative 2340.0003 properly diluted with water.

Queste note sono frutto della nostra migliore esperienza. Tuttavia essendo molti gli impieghi e le tecniche di applicazione non possiamo assumere garanzie per ogni singolo caso.
 These applicative notes are given to the best of our experience. However being many uses and application technics we can not guarantee for each single case.

Apply the first coat of Riff Base coat uniformly on the surface with a plastic trowel on the entire surface. Work immediately the surface with the same trowel with irregular movements, using the flat part of the trowel, until obtaining a slightly aging effect. After 6 -8 hours apply a second coat of EP!C RIFF Base Coat always with the plastic trowel. Work the product irregularly and make sure to leave some empty spaces that are typical of this decorative effect. Wait few minutes and lightly smooth the picks on the surface.

When the surface is totally dry apply two coats of EP!C RIFF Finish by brush, then work the surface with a sponge trowel using circular movements, when the paint is still wet, in order to uniformly spread the product. Wait at least 6 hours within the two coats.

After each coat of EP!C RIFF finish, work the surface with the plastic trowel, in order to remove the excess of paint and in order to empathise the depth of the decorative effect.

ALREADY PAINTED WALLS – make sure that the old paint is well anchored and of good quality. In case of chalking paint it is necessary to remove the old paint and to use a fixative as per the “New Walls” section.

Note

Brushes and tools must be washed with water immediately after the use. Keep the product away from frost.

Stability

The finished product, if stored in a dry environment, in well closed buckets, with temperature within 5 e 30°C , does not have any problem of stability. The life time of the product is 12 month.

27/03/2015